AL.P.A.S. S.R.L. | Revision nr. 1 | | Dated 07/02/2017 | | Printed on 07/02/2017 | | Page n. 1/12

Safety data sheet

SECTION 1. Identification of the substance/mixture and of the company/undertaking.

1.1. Product identifier.

Product name.

MASTIK PRO
Chemical name and synonym.

MASTIK PRO
natural rubber latex

1.2. Relevant identified uses of the substance or mixture and uses advised against.

Intended use. Not available

1.3. Details of the supplier of the safety data sheet.

Name. AL.P.A.S. S.R.L.

Full address. Strada Statale 10 Padana Ovest Zona Industriale

District and Country. 15029 Solero (AL)

ITALIA

Tel. +39-0131-217408 Fax. +39-0131-217943

e-mail address of the competent person.

responsible for the Safety Data Sheet. laboratorio@alpas.eu

1.4. Emergency telephone number.

For urgent inquiries refer to. Centro Antiveleni di Torino 011 6637637 (CAV Ospedale Molinette - Torino)

Centro Antiveleni di Milano 02 66101029 (CAV Ospedale Niguarda Ca` Granda -Milano) Centro Antiveleni di Pavia 0382 24444 (CAV IRCCS Fondazione Maugeri - Pavia) Centro Antiveleni di Bergamo 800 883300 (CAV Ospedali Riuniti - Bergamo) Centro Antiveleni di Firenze 055 7947819 (CAV Ospedale Careggi - Firenze) Centro Antiveleni di Roma 06 3054343 (CAV Policlinico Gemelli - Roma) Centro Antiveleni di Roma 06 49978000 (CAV Policlinico Umberto I - Roma) Centro Antiveleni di Napoli 081 7472870 (CAV Ospedale Cardarelli - Napoli)

SECTION 2. Hazards identification.

2.1. Classification of the substance or mixture.

The product is classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of EC Regulation 1907/2006 and subsequent amendments. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Skin sensitization, category 1 H317 May cause an allergic skin reaction.

2.2. Label elements.

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

AL.P.A.S. S.R.L.

TS - TYRE SEALANT

Revision nr. 1

Dated 07/02/2017

Printed on 07/02/2017

Page n. 2/12

Hazard pictograms:



Signal words: Warning

Hazard statements:

H317 May cause an allergic skin reaction.

Precautionary statements:

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves.

P302+P352 IF ON SKIN: wash with plenty of water / . . .

P362+P364 Take off contaminated clothing and wash it before reuse.

Contains:

2.3. Other hazards.

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

SECTION 3. Composition/information on ingredients.

3.1. Substances.

Information not relevant.

3.2. Mixtures.

Contains:

The full wording of hazard (H) phrases is given in section 16 of the sheet.

Identification.

Classification 1272/2008

(CLP).

CAS. 9006-04-6 $30 \le x < 50$ Skin Sens. 1 H317

EC. 232-689-0 INDEX. -ETHANEDIOL

CAS. 107-21-1 $1 \le x < 5$ Acute Tox. 4 H302, STOT RE

2 H373

EC. 203-473-3 INDEX. 603-027-00-1

Reg. no. 01-2119456816-28-xxxx

SECTION 4. First aid measures.

AL.P.A.S. S.R.L. | Revision nr. 1 | | Dated 07/02/2017 | | Printed on 07/02/2017 | | Page n. 3/12 |

4.1. Description of first aid measures.

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Wash immediately with plenty of water. If irritation persists, get medical advice/attention. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. In the event of breathing difficulties, get medical advice/attention immediately.

INGESTION: Get medical advice/attention. Induce vomiting only if indicated by the doctor. Never give anything by mouth to an unconscious person, unless authorised by a doctor.

4.2. Most important symptoms and effects, both acute and delayed.

Specific information on symptoms and effects caused by the product are unknown. For symptoms and effects caused by the contained substances, see chap. 11.

4.3. Indication of any immediate medical attention and special treatment needed.

Information not available

SECTION 5. Firefighting measures.

5.1. Extinguishing media.

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray. UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture.

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE Do not breathe combustion products.

5.3. Advice for firefighters.

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures.

6.1. Personal precautions, protective equipment and emergency procedures.

AL.P.A.S. S.R.L. Revision nr. 1 Dated 07/02/2017 Printed on 07/02/2017 Page n. 4/12

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions.

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up.

Collect the leaked product into a suitable container. If the product is flammable, use explosion-proof equipment. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections.

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage.

7.1. Precautions for safe handling.

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

7.2. Conditions for safe storage, including any incompatibilities.

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s).

Information not available.

SECTION 8. Exposure controls/personal protection.

8.1. Control parameters.

Regulatory References:

DEU	Deutschland	MAK-und BAT-Werte-Liste 2012
EDA	Eranco	IOPE nº0100 du 10 mai 2012 nage 877

FRA France JORF n°0109 du 10 mai 2012 page 8773 texte n° 102

GBR United Kingdom EH40/2005 Workplace exposure limits ITA Italia Decreto Legislativo 9 Aprile 2008, n.81

POL Polska ROZPORZĄDZENIE MINISTRA PRACY I POLITYKI SPOŁECZNEJ z dnia

16 grudnia 2011r

AL.P.A.S. S.R.L.

TS - TYRE SEALANT

Revision nr. 1

Dated 07/02/2017

Printed on 07/02/2017

Page n. 5/12

PRT Portugal

Ministério da Economia e do Emprego Consolida as prescrições mínimas

em matéria de protecção dos trabalhadores contra os riscos para a

segurança e a saúde devido à exposição a agentes químicos no trabalho -

Diaro da Republica I 26; 2012-02-06

EU OEL EU

Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC;

Directive 2000/39/EC.

TLV-ACGIH ACGIH 2016

ETHANEDIOL

Threshold Limit Value Type	Country	TWA/8h		STEL/15min			
		mg/m3	ppm	mg/m3	ppm		
AGW	DEU	26	10	52	20	SKIN.	
MAK	DEU	26	10	52	20	SKIN.	
VLEP	FRA	52	20	104	40	SKIN.	
WEL	GBR	52	20	104	40		
VLEP	ITA	52	20	104	40	SKIN.	
NDS	POL	15		20			
VLE	PRT	52	20	104	40	SKIN.	
OEL	EU	52	20	104	40	SKIN.	
TLV-ACGIH		10					
Predicted no-effect concentration - PNEC.							
Normal value in fresh water Normal value in marine water Normal value for fresh water sediment Normal value of STP microorganisms Normal value for the terrestrial compartment			10 1 20,9 10 1,53		mg/l mg/l mg/kg mg/l mg/kg		
Health - Derived no-effect level - DNEL / DMEL							

Health - Derived no-effect level - DNEL / DMEL								
	Effects on				Effects on			
	consumers.				workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic	Acute local	Acute	Chronic local	Chronic
				systemic		systemic		systemic
Inhalation.	7 mg/m^3	VND					35 mg/m^3	VND
Skin.			VND	53 mg/kg			VND	106 mg/kg

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

8.2. Exposure controls.

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration. Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

AL.P.A.S. S.R.L. Revision nr. 1 Dated 07/02/2017 Printed on 07/02/2017 Page n. 6/12

SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type B filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS.

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties.

9.1. Information on basic physical and chemical properties.

Appearance liquid Colour red Odour typical Not available. Odour threshold. Not available. Melting point / freezing point. Not available. Initial boiling point. Not available Boiling range. Not available. Flash point. Not available. Evaporation Rate Not available. Flammability of solids and gases Not available. Lower inflammability limit. Not available. Upper inflammability limit. Not available. Not available. Lower explosive limit. Upper explosive limit. Not available Vapour pressure. Not available. Vapour density Not available. Relative density. Not available. Solubility Partition coefficient: n-octanol/water Not available. Not available. Auto-ignition temperature. Decomposition temperature. Not available Viscosity Not available. Explosive properties Not available. Not available. Oxidising properties

9.2. Other information.

 VOC (Directive 2010/75/EC):
 0

 VOC (volatile carbon):
 0

 Viscosity at 25°C [mPa.s]
 300

SECTION 10. Stability and reactivity.

AL.P.A.S. S.R.L. | Revision nr. 1 | | Dated 07/02/2017 | | Printed on 07/02/2017 | | Page n. 7/12

10.1. Reactivity.

There are no particular risks of reaction with other substances in normal conditions of use.

ETHANEDIOL

In the air absorbs moisture. Decomposes at temperatures above 200°C/392°F.

10.2. Chemical stability.

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions.

No hazardous reactions are foreseeable in normal conditions of use and storage.

ETHANEDIOL

Risk of explosion on contact with: perchloric acid.May react dangerously with: chlorosulphuric acid,sodium hydroxide,sulphuric acid,phosphorus pentasulphide,chromium (III) oxide,chromyl chloride,potassium perchlorate,potassium dichromate,sodium peroxide,aluminium.Forms explosive mixtures with: air.

10.4. Conditions to avoid.

None in particular. However the usual precautions used for chemical products should be respected.

ETHANEDIOL

Avoid exposure to: sources of heat,naked flames.

10.5. Incompatible materials.

Information not available.

10.6. Hazardous decomposition products.

ETHANEDIOL

May develop: hydroxyacetaldehyde,glyoxal,acetaldehyde,methane,carbon monoxide,hydrogen.

SECTION 11. Toxicological information.

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

AL.P.A.S. S.R.L.

Revision nr. 1

Dated 07/02/2017

Printed on 07/02/2017

Page n. 8/12

TS - TYRE SEALANT

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on toxicological effects.

ETHANEDIOLFollowing ingestion it initially stimulates the CNS; later on depression results. Renal damage with anuria and uremia may occur. Symptoms of over exposure are: vomiting, somnolence, difficulty in breathing, convulsions. The lethal dose in man is approximately 1,4 l/kg. The way of entry is inhalation and ingestion.

ACUTE TOXICITY.

LC50 (Inhalation - vapours) of the mixture: Not classified (no significant component).

LC50 (Inhalation - mists / powders) of the mixture: Not classified (no significant component).

LD50 (Oral) of the mixture:>2000 mg/kg

LD50 (Dermal) of the mixture: Not classified (no significant component).

ETHANEDIOL

LD50 (Oral).> 2000 mg/kg Rat

LD50 (Dermal).9530 mg/kg Rabbit

LC50 (Inhalation).> 2,5 mg/l Rat 6h

SKIN CORROSION / IRRITATION.

Does not meet the classification criteria for this hazard class.

SERIOUS EYE DAMAGE / IRRITATION.

Does not meet the classification criteria for this hazard class.

RESPIRATORY OR SKIN SENSITISATION.

Sensitising for the skin.

GERM CELL MUTAGENICITY.

Does not meet the classification criteria for this hazard class.

CARCINOGENICITY.

Does not meet the classification criteria for this hazard class.

REPRODUCTIVE TOXICITY.

Does not meet the classification criteria for this hazard class.

STOT - SINGLE EXPOSURE.

Does not meet the classification criteria for this hazard class.

STOT - REPEATED EXPOSURE.

Does not meet the classification criteria for this hazard class.

ASPIRATION HAZARD.

Does not meet the classification criteria for this hazard class.

SECTION 12. Ecological information.

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

12.1. Toxicity.

ETHANEDIOL

LC50 - for Fish. 72860 mg/l/96h
EC50 - for Crustacea. > 100 mg/l/48h

12.2. Persistence and degradability.

ETHANEDIOL

Solubility in water. 1000 - 10000 mg/l

Rapidly biodegradable.

AL.P.A.S. S.R.L.	Revision nr. 1
,	Dated 07/02/2017
TS - TYRE SEALANT	Printed on 07/02/2017
	Page n. 9/12
12.3. Bioaccumulative potential.	
ETHANEDIOL	
Partition coefficient: n1,36	
octanol/water.	
12.4. Mobility in soil.	
12.4. Mobility III doll.	
Information not available.	
12.5. Results of PBT and vPvB assessment.	
12.0. Results of FBT and WVB assessment.	
On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.	
12.6. Other adverse effects.	
12.0. Other auverse effects.	
Information not available.	
CECTION 42 Diamond considerations	
SECTION 13. Disposal considerations.	
13.1. Waste treatment methods.	
Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of wast evaluated according to applicable regulations.	e containing this product should be
Disposal must be performed through an authorised waste management firm, in compliance with national and local reg CONTAMINATED PACKAGING	ulations.
Contaminated packaging must be recovered or disposed of in compliance with national waste management regulation	s.
SECTION 14. Transport information.	
The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods b	y Road (ADR) and by Rail (RID), of
the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) r	
14.1. UN number.	
Not applicable.	
14.2. UN proper shipping name.	
Not applicable.	
14.3. Transport hazard class(es).	

AL.P.A.S. S.R.L.	Revision nr. 1
	Dated 07/02/2017
TS - TYRE SEALANT	Printed on 07/02/2017
	Page n. 10/12
Not applicable.	
то артоль.	
14.4. Packing group.	
Not applicable.	
14.5. Environmental hazards.	
Not applicable.	
44.C. Onesial annualities for user	
14.6. Special precautions for user.	
Not applicable.	
14.7. Transport in bulk according to Annex II of Marpol and the IBC Code.	
Information not relevant.	
OFOTION 45. De suelete sue information	
SECTION 15. Regulatory information.	
15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture.	
Seveso Category - Directive 2012/18/EC:	
Geveso Galegory - Directive 2012/10/EG.	
Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006.	
Product.	
Point. 3	
Substances in Candidate List (Art. 59 REACH).	
Substances in Surdidute List (Airt. 55 NEAGT).	
On the basis of available data, the product does not contain any SVHC in percentage greater than 0,1%.	
Substances subject to authorisarion (Annex XIV REACH).	
Non-	
None.	
Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:	
None.	
Substances subject to the Rotterdam Convention:	

Revision nr. 1 AL.P.A.S. S.R.L. Dated 07/02/2017 Printed on 07/02/2017 TS - TYRE SEALANT Page n. 11/12

None.

Substances subject to the Stockholm Convention:

None.

Healthcare controls.

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

15.2. Chemical safety assessment.

No chemical safety assessment has been processed for the mixture and the substances it contains.

SECTION 16. Other information.

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Acute Tox. 4 Acute toxicity, category 4

STOT RF 2 Specific target organ toxicity - repeated exposure, category 2

Skin Sens. 1 Skin sensitization, category 1

H302 Harmful if swallowed.

H373 May cause damage to organs through prolonged or repeated exposure.

H317 May cause an allergic skin reaction.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
 WGK: Water hazard classes (German).

AL.P.A.S. S.R.L.	Revision nr. 1
	Dated 07/02/2017
TS - TYRE SEALANT	Printed on 07/02/2017
	Page n. 12/12

GENERAL BIBLIOGRAPHY

- 1. Regulation (EU) 1907/2006 (REACH) of the European Parliament
- 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
- 3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
- 4. Regulation (EU) 2015/830 of the European Parliament
- 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
- 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
- 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
- 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- 10. Regulation (EÚ) 2015/1221 (VII Atp. CLP) of the European Parliament
- The Merck Index. 10th Edition
- Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- ECHA website

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.